



Description de produit

- Onduleur KSTAR affichage écran LCD
- Tension Entrée 220/230/240V
- Fréquence Entrée 50/60Hz
- Tension Sortie 220/230/240V
- LAN Internet Protection
- Fréquence Sortie 50/60 Hz
- chargement automatique en mode désactivé
- Compatible avec le groupe électrogène
- Configuration 12V DC voltage
- Recharge 90% Capacité après huit heures

Fonctionnalités

- Puissance nominale : 1500VA
- Puissance active : 900W
- Fonction de démarrage à froid
- Interface RS232 / USB intelligente pour la gestion de l'alimentation
- Fonction d'autodiagnostic intégrée
- Protection Internet Modem / LAN
- Compatible avec générateur
- Panneau LCD pour l'option
- Capacité de charge la plus rapide
- Chargement automatique en mode arrêt
- Fonction de redémarrage automatique

MICROPOWER SERIES Technical Specifications

MODEL	Micro 400	Micro 600	Micro 800	Micro 1000	Micro 1200	Micro 1500	Micro 2000
Capacity (VA/Watts)	400 / 240	600 / 360	800 / 480	1000 / 600	1200 / 720	1500 / 900	2000 / 1200
INPUT							
Nominal input voltage	110/120 Vac or 220/230/240 Vac						
Operating voltage range	81 ~ 145 Vac / 162 ~ 290 Vac						
Operating frequency range	50/60 Hz (± 10%)						
OUTPUT							
Output voltage range (Batt. Mode)	Simulated sine wave at nominal voltage ± 10%						
Frequency range (Batt. Mode)	50 or 60Hz ± 1Hz						
Transfer time	Typical 2~6 ms, 10ms max.						
BATTERY							
Battery type & number	12 V/4.5Ah x 1	12 V/7Ah x 1	12 V/9Ah x 1	12V/7Ah x 2	12 V/7Ah x 2	12 V/9Ah x 2	12 V/9Ah x 2
Typical recharge time	6~8 hours (to 90% of full capacity)						
SYSTEM FEATURES							
Protection	Overload and overcharge protection						
Communication interface	USB/RS-232 (optional),Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC						
ENVIRONMENTAL							
Operating temperature	0 ~ 40 °C						
Humidity range	0 ~ 95%(non-condensing)						
Noise level	<40dB (1 meter from surface)						
PHYSICAL							
Dimension D × W × H (mm)	298 × 101 × 142			338 × 149.3 × 162		380 × 158 × 198	

Specifications are subject to change without prior notice.